



iPhone 6 Plus iSclack Opening Procedure

Prereq for display assembly.

Written By: Walter Galan



INTRODUCTION

Prereq for display assembly.



TOOLS:

- [iSclack](#) (1)
-

Step 1 — iSclack Opening Procedure



i The next two steps demonstrate using the [iSclack](#), a great tool for safely opening the iPhone 6 Plus that we recommend for anyone doing more than one repair. **If you aren't using the iSclack, skip to Step 4.**

- If the plastic depth gauge is attached at the center of the iSclack, remove it now—it's not needed for larger phones like the iPhone 6 Plus.
- Close the handle on the iSclack, opening the suction cup jaws.
- Place the bottom of your iPhone in between the suction cups.
- i** Position the iSclack's upper suction cup against the display, near the home button.
- Open the handles to close the jaws of the iSclack. Center the suction cups and press them firmly onto the top and bottom of the iPhone.

Step 2



- Hold onto your iPhone securely and close the handle of the iSclack to separate the suction cups, pulling the front panel up from the rear case.
- ⓘ The iSclack is designed to safely open your iPhone enough to separate the pieces, but not enough to damage any of the display cables.
- Peel the two suction cups off your iPhone.
- **Skip the next three steps and continue on to Step 7.**

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-23 12:47:07 AM.